



Size Table

No	Description	Coiled OD	Coiled ID	Cut length L
01	35-260	0.89mm	0.55mm	260cm
02	35-150	0.89mm	0.55mm	150cm

General requirements:

基本要求

- 304V Stainless round wire, bare wire size: 0.165mm±0.005mm
304V不锈钢材质，圆丝，裸丝直径：0.165mm±0.005mm
Medical grade PTFE coated , color: Green, Coated wire OD: 0.170mm±0.005mm
表面医疗级PTFE涂层，颜色绿色，涂层后的线外径：0.170mm±0.005mm
- Spring should be smooth, free of ripples, or burrs
绕制的弹簧圈需要光滑，没有毛刺，杂质等
- Spring should meet requirements of ISO 11070 Annex F and G
绕制后的弹簧圈对涂层性能没有改变，应满足标准ISO 11070 Annex F and G
- Free of any peel off or debris visible to 2.5X magnification
在2.5倍放大率下无差，弹簧圈表面涂层没有剥落或毛刺
- Material should be clean, double PE bag packaging
弹簧圈需要双层PE袋子包装
- CoC should be shipped with the material, CoC should contain test report
随货需提供出厂检验报告和一致性申明

	(签名)	(日期)				广州启骏生物科技有限公司		
绘制		2018/10/31				Title	Coated Spring	
审核			A/0		初始发放	2018/10/31	Doc No.	RM020610
批准			版本		更改内容	日期	比例:NA	版本:A/0 Page 1/1

This document contains information proprietary to Guangzhou Qijun Biotech. It shall not be reproduced in whole or part by any means unless authorized in writing by a representative of Guangzhou Qijun Biotec